

NEEDLE VALVE MANIFOLDS WITH TRANSPORT FRAMES

DURAPAC **VMN-SERIES** NEEDLE VALVE MANIFOLDS WITH TRANSPORT FRAMES ARE DESIGNED TO BE USED WITH 10,150 PSI HAND PUMPS AND POWER UNITS.

They offer a convenient solution for operating multiple cylinders from a single input source. Each manifold includes FGA-1 gauge adaptors, and PG-63 liquid filled 2.5" diameter pressure gauges. Versions with CR-6 female couplers on the input and output ports are available. All ports are 3/8" NPT female.



VMN-8M-GFC

VMN-4M-GFC

| Model Number | Control Outlets | Qty. PG-63 Included | Qty. FGA-1 Included | Qty. CR-6 Included | Pressure Rating (psi) | Width (in) | Height (in) | Depth (in) | Net Weight (lbs) |
|--------------|-----------------|---------------------|---------------------|--------------------|-----------------------|------------|-------------|------------|------------------|
| VMN-2M-GF | 2 | 2 | 2 | - | 10,150 | 14.57 | 11.02 | 7.09 | 15.1 |
| VMN-2M-GFC | 2 | 2 | 2 | 3 | 10,150 | 14.57 | 11.02 | 7.09 | 17.5 |
| VMN-4M-GF | 4 | 4 | 4 | - | 10,150 | 14.57 | 11.02 | 7.09 | 22.6 |
| VMN-4M-GFC | 4 | 4 | 4 | 5 | 10,150 | 14.57 | 11.02 | 7.09 | 24.8 |
| VMN-6M-GF | 6 | 6 | 6 | - | 10,150 | 21.06 | 11.02 | 7.09 | 27.8 |
| VMN-6M-GFC | 6 | 6 | 6 | 7 | 10,150 | 21.06 | 11.02 | 7.09 | 30.9 |
| VMN-8M-GF | 8 | 8 | 8 | - | 10,150 | 26.97 | 11.02 | 7.09 | 29.1 |
| VMN-8M-GFC | 8 | 8 | 8 | 9 | 10,150 | 26.97 | 11.02 | 7.09 | 37.5 |