

DURAPAC **HYDRAULIC COUPLINGS** OFFER THE USER VARIOUS OPTIONS FOR EASY ASSEMBLY AND CONNECTION OF HYDRAULIC SYSTEMS AND TOOLS.

The CR-6 female high flow screw coupling with dust cap is standard supply on all Durapac cylinders. Other options available include 1/8" and 1/4" screw style couplings and snap together style where no oil spill on connection or disconnection is desirable. The GCS-210 is a gauge coupling set and is ideal for use when the pressure gauge needs to be removed from a system for protection and transportation.



THREAD SIZES

**1/8", 1/4" & 3/8"-NPT,
9/16"-18UNF,
3/4"-16UNF**

MAXIMUM OPERATING PRESSURE RANGE

700 – 4,000 bar

J

SYSTEM ACCESSORIES

CH-2
1/8" male coupling with dust cap* (1/8"-NPT male)

CR-2
1/8" female coupling with dust cap* (1/8"-NPT male)

CS-2
Coupling set with dust caps* includes CH-2 and CR-2

CH-4
1/4" male coupling with dust cap* (1/4"-NPT female)

CR-4
1/4" female coupling with dust cap* (1/4"-NPT male)

CS-4
Coupling set with dust caps* includes CH-4 and CR-4

CH-6
3/8" male coupling with dust cap* (3/8"-NPT female)

CR-6
3/8" female coupling with dust cap* (3/8"-NPT male)

CS-6
Coupling set with dust caps* includes CH-6 and CR-6

UDC-1
Universal dust cap to suit 3/8" male and female couplings

GCS-210
Gauge coupling set with dust caps. Compact pin design

1/4"-NPT male
1/4"-NPT female

CFH-6
Male half snap coupling with dust cap (3/8"-NPT female)

CFR-6
Female half snap coupling with dust cap (3/8"-NPT female)

CFS-6
Snap coupling set with dust caps includes CFH-6 and CFR-6