

## HYDRAULIC COUPLINGS

DURAPAC **HYDRAULIC COUPLINGS** OFFER THE USER VARIOUS OPTIONS FOR EASY ASSEMBLY AND CONNECTION OF HYDRAULIC SYSTEMS AND TOOLS.

The CR-6 female high flow screw coupling with plastic dust cap is standard supply on all Durapac cylinders. Other options available include 1/8" and 1/4" screw style couplings, metal dust caps and snap together style where no oil spill on connection or disconnection is desirable. The GCS-210 is a gauge coupling set and is ideal for use when the pressure gauge needs to be removed from a system for protection and transportation.

<b>CH-2</b> 1/8" male coupling with dust cap* (1/8"-NPT male) 	<b>CR-2</b> 1/8" female coupling with dust cap* (1/8"-NPT male) 	<b>CS-2</b> Coupling set with dust caps* includes CH-2 and CR-2 	 <b>THREAD SIZES</b> 1/8", 1/4" & 3/8"-NPT, 9/16"-18UNF, 3/4"-16UNF <b>MAXIMUM OPERATING PRESSURE RANGE</b> 700 – 4,000 bar	
<b>CH-4</b> 1/4" male coupling with dust cap* (1/4"-NPT female) 	<b>CR-4</b> 1/4" female coupling with dust cap* (1/4"-NPT male) 	<b>CS-4</b> Coupling set with dust caps* includes CH-4 and CR-4 		
<b>CH-6</b> 3/8" male coupling with dust cap* (3/8"-NPT female) 	<b>CR-6</b> 3/8" female coupling with dust cap* (3/8"-NPT male) 	<b>CS-6</b> Coupling set with dust caps* includes CH-6 and CR-6 	<b>UDC-1</b> Universal dust cap to suit 3/8" male and female couplings 	
<b>GCS-210</b> Gauge coupling set with dust caps. Compact pin design  1/4"-NPT male 1/4"-NPT female	<b>CFH-6</b> Male half snap coupling with dust cap (3/8"-NPT female) 	<b>CFR-6</b> Female half snap coupling with dust cap (3/8"-NPT female) 	<b>CFS-6</b> Snap coupling set with dust caps includes CFH-6 and CFR-6 	

\* Dust cap not shown

J

SYSTEM ACCESSORIES