

NEEDLE VALVE MANIFOLDS WITH TRANSPORT FRAMES

DURAPAC **VMN-SERIES** NEEDLE VALVE MANIFOLDS WITH TRANSPORT FRAMES ARE DESIGNED TO BE USED WITH 700 BAR HAND PUMPS AND POWER UNITS.

They offer a convenient solution for operating multiple cylinders from a single input source. Each manifold includes FGA-1 gauge adaptors, and PG-63 liquid filled 63 mm diameter pressure gauges. Versions with CR-6 female couplers on the input and output ports are available. All ports are 3/8" NPT female.



VMN-8M-GFC

VMN-4M-GFC

Model Number	Control Outlets	Qty. PG-63 Included	Qty. FGA-1 Included	Qty. CR-6 Included	Pressure Rating (bar)	Width (mm)	Height (mm)	Depth (mm)	Net Weight (kg)
VMN-2M-GF	2	2	2	-	700	370	280	180	6.85
VMN-2M-GFC	2	2	2	3	700	370	280	180	7.95
VMN-4M-GF	4	4	4	-	700	370	280	180	10.25
VMN-4M-GFC	4	4	4	5	700	370	280	180	11.25
VMN-6M-GF	6	6	6	-	700	535	280	180	12.60
VMN-6M-GFC	6	6	6	7	700	535	280	180	14.00
VMN-8M-GF	8	8	8	-	700	685	280	180	13.20
VMN-8M-GFC	8	8	8	9	700	685	280	180	17.00